

OFFICIAL

DOCKET: CU-3411

**RECEIVED
IN THE UNITED STATES PATENT AND TRADEMARK OFFICE CENTRAL FAX CENTER**

APPLICANT: Roland Starck et al

AUG 16 2004

SERIAL NO: 10/691,322

) Group Art Unit: 3742

FILED: October 22, 2003

) Examiner: Vinod D. Patel

TITLE: ELECTRIC HEATING ARRANGEMENT

AMENDED CLAIMS

1. (currently amended) Electric heating arrangement having a tubular housing in which is provided at least one PTC heating element and at least one pair of metallic heat dissipators between which the at least one heating element is clamped and which for this purpose each comprise a base portion facing the at least one heating element and one or two curved legs projecting from said base portion, which adapt themselves resiliently to the inner surface of the surrounding wall of the housing, wherein the housing is deformed by the legs of the heat dissipators applied resiliently against the surrounding wall of the housing, and the legs taper toward their free ends.
2. (previously presented) The heating arrangement as defined in Claim 1, wherein the base portion is thicker than the legs projecting from it.
3. (currently amended) Electric heating arrangement having a tubular housing in which is provided at least one PTC heating element and at least one pair of metallic heat dissipators between which the at least one heating element is clamped and which for this purpose each comprise a base portion facing the at least one heating element and one or two curved legs projecting from said base portion, which adapt themselves resiliently to the inner surface of the surrounding wall of the housing, wherein the housing is deformed by the legs of the heat dissipators applied resiliently against the surrounding wall of the housing, and the base portion is thicker than the legs projecting from it.
4. (previously presented) The heating arrangement as defined in Claim 3, wherein the legs taper toward their free ends.

5. (previously presented) The heating arrangement as defined in Claims 1 or 3, wherein the legs taper continuously over their full length.
6. (currently amended) The heating arrangement as defined in Claim 5, wherein the legs taper ~~regularly~~ uniformly.
7. (previously presented) The heating arrangement as defined in Claims 1 or 3, wherein the base portion has the greatest thickness in the middle between the legs projecting from it.
8. (previously presented) The heating arrangement as defined in Claims 1 or 3, wherein two extensions extending in the longitudinal direction of the housing are formed on the base portion, on its side facing away from the heating element, which extensions form a terminal of U-shaped cross-section for a power supply cable.
9. (previously presented) The heating arrangement as defined in Claims 1 or 3, wherein the base portion exhibits a flat, especially a plane, configuration on its side facing the PTC heating element.
10. (previously presented) The heating arrangement as defined in Claims 1 or 3, wherein the surrounding wall of the housing is thinner than the base portion and the legs.
11. (previously presented) The heating arrangement as defined in Claims 1 or 3, wherein the wall thickness of the housing is 0.1 mm to 0.7 mm.
12. (cancelled)
13. (previously presented) The heating arrangement as defined in Claims 1 or 3, wherein the heat dissipators consist of aluminium or an aluminium alloy.
14. (previously presented) The heating arrangement as defined in Claim 13, wherein the heat dissipators are made from an extruded profile material.
15. (previously presented) The heating arrangement as defined in Claims 1 or 3, wherein for mounting the heating elements the housing comprises an open end with an integrally formed flange which can then be closed after assembly.
16. (previously presented) The heating arrangement as defined in Claim 15, wherein a plastic cap is held on the flange of the housing.
17. (previously presented) The heating arrangement as defined in Claim 16, wherein a sealing ring is arranged between the plastic cap and the flange.
18. (previously presented) The heating arrangement as defined in Claims 1 or 3, wherein the housing consists of stainless steel.

19. (previously presented) The heating arrangement as defined in Claims 1 or 3, wherein the legs together cover almost the whole inner surface of the surrounding wall of the housing.

20. (previously presented) The heating arrangement as defined in Claims 1 or 3, wherein the wall thickness of the housing is 0.2 mm to 0.5 mm.